

Cody-3 Thermal Printing Kit

Thermal Printer by GA International
with LabelLive Barcoding Software

NEW!



The GA Cody-3™ Thermal Printer Kit

The Cody-3 desktop thermal printer is capable of printing high-quality 300 dpi text, barcodes, and graphics on many label types and configurations. It can print directly on thermal media or in thermal-transfer mode using an ink ribbon. Professional looking labels can be created and customized with the easy-to-use software (included). This software simplifies the label design process, offering intuitive functionalities that pair perfectly with the Cody-3 printer. Multiple connectivity options are also included.

Simple, Robust, & Affordable

- Accepts label rolls up to 4.64" wide
- User-friendly label design software interface for PC and Mac
- Built-in Database connectivity at no extra cost
- 300 dpi print resolution, for small label printing
- Direct thermal or thermal-transfer modes available
- USB, serial, parallel, and ethernet interface option



What's in the Box

- › Cody-3 printer
- › Power cord*
- › Power adapter
- › USB cable
- › Cardboard take-up core
- › Ribbon holder and take-up spools
- › One Computer Application License for LabelLive Professional

*The product includes a North American, European, or UK power cord and adapter. Other country-specific power cords must be purchased locally and separately.



Technical Specifications

- › **Print Method:** Thermal-Transfer/Direct Thermal
- › **Print Resolution:** 300 dpi
- › **Interfaces:** USB, Serial, Ethernet
- › **Print Speed:** Up to 4" (102 mm/s)
- › **Max. Print Width:** 4.16" (105.7 mm)
- › **Max. Print Length:** 30" (762 mm)
- › **Label Width:** 1" - 4.64" (25.4 - 118 mm)
- › **Label Height:** 0.157" - 30" (4 - 762 mm)
- › **Media Types:** Continuous, Die-Cut/Gap Labels (Black Mark, Notch), Fanfold
- › **Media Width:** 1" - 4.64" (25.4 - 118 mm)
- › **Media Roll Core Size:** 1"
- › **Media Maximum Roll OD:** 5" (127 mm)
- › **Ribbon Maximum OD:** 2.67" (68 mm)
- › **Ribbon Maximum Length:** 984' (300 m)
- › **Ribbon Core Size:** 1" (25.4 mm)
- › **Ribbon Width:** Min. 1.18" (30 mm), Max. 4.3" (110 mm)
- › **Ribbon Winding:** Ink Side Out (ISO)



Shop now on
www.Labtag.com