

Patent Pending

New!

PinTAG™

-196°C

Cryo Labels for 2D-Barcoded Tubes

Temperature range from -196°C to +110°C (-321°F to + 230°F)

- Label both the side and bottom of automated storage tubes
- Print custom information, no need for pre-engraved vials
- Easily re-label tubes with barcodes and readable text
- Compatible with automated sample storage and handling systems



The Ideal Labeling Solution When Sampling Specimen Libraries

Cryogenic PinTAG™ labels are designed to simultaneously identify the side and bottom of slim profile automated sample storage tubes, such as Matrix™ and Simport® tubes. They are fully compatible with automated sample readers/scanners, inventory management software, and automatic/robotic liquid handling systems for use with high-throughput applications. Thermal-transfer printable, these patent pending cryo labels can be printed with 1D/2D barcodes, variable data, graphic images and human-readable text. The ideal labeling solution when sampling or aliquoting specimen libraries, where custom information needs to be encoded onto the receiving vials, providing the user maximum control over the encoded information.

SKU#	W x H (Inches)	W x H (mm)	Core	Labels/Roll
JTTA-553NPSBC1-4WH	1.26" x 0.3"	32 x 7.6mm	1"	4,000
JTTA-553NPSBC3-8WH	1.26" x 0.3"	32 x 7.6mm	3"	8,000

 Shop on [Labtag.com/pintag](https://www.Labtag.com/pintag)