

# Printers, Scanners & Software




## Thermal-Transfer & Direct Thermal Printers

These printers are well-suited to laboratory environments and can be provided with options according to specifications. Printers of other brands, models, and configurations are available. [Shop on labtag.com/printers](https://www.labtag.com/printers)



Printers	Item#	Description
	ZD621t	<p><b>Zebra ZD621t Desktop Printer (300 dpi resolution)</b></p> <ul style="list-style-type: none"> <li>• Print Method: Thermal-Transfer/Direct Thermal</li> <li>• Print Speed: 6 in/s (152mm/s)</li> <li>• Interfaces: USB, Serial, Bluetooth (BTLE5), and Ethernet</li> <li>• Print width up to 4.27" (108mm)</li> <li>• Media core diameter: 1" (25.4 mm)</li> <li>• Optional add-ons: Peeler, Cutter, 4.3" full color touch LCD display, WiFi connectivity</li> <li>• Platform Supported: Windows</li> </ul>
	MACH1	<p><b>cab MACH1 Desktop Printer (300 dpi resolution)</b></p> <ul style="list-style-type: none"> <li>• Print Method: Thermal-Transfer/Direct Thermal</li> <li>• Print Speed: 4 in/s (102mm/s)</li> <li>• Interfaces: USB, Serial (RS232C), Ethernet 10/100</li> <li>• Print width up to 4.25" (108mm)</li> <li>• Media core diameter: 1" (25.4mm)</li> <li>• Optional add-ons: Cutter, Present Sensor (Peeler), External Unwinder</li> <li>• Platform Supported: Windows</li> </ul>
	ZT231	<p><b>Zebra ZT231 Industrial Printer (300 dpi resolution)</b></p> <ul style="list-style-type: none"> <li>• Print Method: Thermal-Transfer/Direct Thermal</li> <li>• Print Speed: up to 12 in/s (304mm/s)</li> <li>• Interfaces: Parallel, Serial, USB, Ethernet, USB Host</li> <li>• Print width up to 4.09" (104mm)</li> <li>• Media core diameter: 3" (76.2mm)</li> <li>• Optional add-ons: Peeler, Cutter, WiFi, UHF RFID</li> <li>• Platform Supported: Windows</li> </ul>
	SQUIX 4 M	<p><b>cab SQUIX 4 M Industrial Printer (300 dpi resolution)</b></p> <ul style="list-style-type: none"> <li>• Print Method: Thermal-Transfer/Direct Thermal</li> <li>• Print Speed: 11.8 in/s (300mm/s)</li> <li>• Interfaces: USB, Serial (RS232C), Ethernet 10/100</li> <li>• Print width up to 4.25" (108mm)</li> <li>• Media core diameter: 3" (76mm)</li> <li>• Optional add-ons: Cutter, Present Sensor (Peeler), External Unwinder and Rewinder, WLAN 802. 11b, g, n.</li> <li>• Platform Supported: Windows</li> <li>• Centered material guide</li> </ul>
	CODY-3	<p><b>Cody-3 Desktop Printer (300 dpi resolution)</b></p> <ul style="list-style-type: none"> <li>• Print Method: Thermal-Transfer/Direct Thermal</li> <li>• Print Speed: 4 in/s (102mm/s)</li> <li>• Interfaces: USB, Serial (RS232C), Ethernet 10/100</li> <li>• Print width up to 4.25" (108mm)</li> <li>• Media core diameter: 1" - 1.5" (25.4 - 38.1 mm)</li> <li>• Optional add-ons: Cutter, Present Sensor (Peeler), External Unwinder and Rewinder, WLAN 802. 11b, g, n.</li> <li>• Platform Supported: Windows</li> <li>• Centered material guide</li> </ul>
	DYMO-LW550	<p><b>DYMO® LabelWriter™ 550 (300 dpi resolution)</b></p> <ul style="list-style-type: none"> <li>• Print Method: Direct Thermal</li> <li>• Print Speed: up to 6"/second</li> <li>• Interfaces: USB</li> <li>• Print width up to 2.25" (56 mm)</li> <li>• Media core diameter: 1" (25.4mm)</li> <li>• Platform Supported: Windows &amp; Mac OS</li> </ul>

# Scanners & Imagers

Barcode scanners for 1-Dimensional and 2-Dimensional barcode scanning & area imaging. [Shop on labtag.com/scanners](https://labtag.com/scanners)

Barcode Scanners	Item #	Description
 <p># 1472G2D-2USB-5-N</p>	1472G2D-2USB-5-N	<p><b>Honeywell Voyager</b></p> <p>Honeywell Voyager 1-D and 2-D barcode area imager scanner, USB and Wireless (Bluetooth)</p> <ul style="list-style-type: none"> <li>Barcode Scanner Type: Imager, 1D and 2D barcodes</li> <li>Cordless/Tethered: Cordless</li> <li>Holder Style: Barcode scanner charging stand</li> <li>Interface: USB, Bluetooth</li> <li>Operating System: Windows, iOS</li> </ul>
 <p>#EVO-SG1-ADU</p>	EVO-SG1-ADU	<p><b>EVO</b></p> <p>POS-X EVO 1-D and 2-D barcode area imager scanner, USB kit with stand</p> <ul style="list-style-type: none"> <li>Barcode Scanner Type: 1D and 2D barcodes</li> <li>Cordless/Tethered: Tethered</li> <li>Holder Style: Stand</li> <li>Interface: USB</li> </ul>
RFID Reader / Barcode Scanners	Item #	Description
 <p>#RFD40-TC22</p>	RFD40-TC22	<p><b>Zebra Handheld UHF RFID Reader with Tri-Function Trigger</b></p> <ul style="list-style-type: none"> <li>Barcode Scanner Type: Imager, 1D and 2D barcodes</li> <li>RFID Operating Frequency: FCC 902-928 MHz (US) / ETSI 865-868 MHz (EU)</li> <li>Standards Supported: EPC Class 1 Gen 2 V2; EPC Gen2 V2</li> <li>Holder Style: Gun Grip</li> <li>Interface: Wi-Fi 6E, Bluetooth, 5G cellular connectivity</li> <li>Operating System: Android 14, upgradeable to Android 16</li> </ul>

# Label Printing Software\*

 <p><b>BarTender</b></p> <ul style="list-style-type: none"> <li>Advanced Text Formatting</li> <li>RFID Capabilities</li> <li>Designer Typefaces</li> <li>Exceptional Design Flexibility</li> <li>"Instant" Barcodes</li> <li>Enhanced Database Connectivity</li> <li>Password Security</li> <li>On-Screen Display</li> <li>Compliance Labels</li> <li>Customized Serialization</li> <li>Custom Data-Entry Forms</li> <li>Industrial Symbols</li> <li>Predefined "Toolbox" Components</li> <li>Customizing Features</li> <li>Technical Support</li> </ul>	 <p><b>ZebraDesigner</b></p> <ul style="list-style-type: none"> <li>Supports native printer fonts</li> <li>Supports Unicode™</li> <li>Supports native barcodes</li> <li>ODBC and ASCII file connectivity</li> <li>GS1-128 wizard</li> <li>RFID wizard</li> <li>KDU support</li> <li>Print to file</li> <li>Simple VB script</li> <li>Print time questions</li> <li>Pick database records at print time</li> <li>Time/Date and RTC</li> <li>CPCL, EPL™ and ZPL (with ZebraDesigner Windows driver version 5)</li> </ul>
---	--

\*Features listed above may vary depending on the software version. Please contact our support team for more information.

[Shop on Labtag.com/software](https://labtag.com/software)