

SnapPEEL™ Technology

Protected Design

Patent Pending

- Quick and easy peeling and application
- Increase labeling speed and efficiency
- Gives a bird's-eye view of labeled tubes
- Perfect for identifying cryo vials and microtubes



1 Peel back the liner and lift the label from the rectangle side



2 Apply the dot label on the vial cap



3 Snap off the rectangular portion of the label



4 Apply the rectangle to the side of the cryo vial

DYMO® LabelWriter™ 5-Series Cryogenic SnapPEEL™ Labels

Temperature Range: -196°C to +70°C (-321°F to +158°F)

CryoSTUCK® labels for frozen surfaces are now available for printing with DYMO LabelWriter 5-Series printers. These DYMO-Branded labels can be printed without ribbons or other ink sources. Ideal for labeling ambient temperature and frozen surfaces, these labels withstand exposure to solvents, water baths, and condensation.

SKU#	Inches (W x H)	mm (W x H)	Labels/Roll	Colors
LWCS-506-WH	0.375" circle + 0.94" x 0.5"	9.5 circle + 23.9 x 12.7	750	WH
LWCS-507-WH	0.437" circle + 1.125" x 0.625"	11.1 circle + 28.6 x 15.9	750	

NEW



NitroTAG® with SnapPEEL™

Temperature Range: -196°C to +110°C (-321°F to +230°F)

Our patent pending SnapPEEL™ technology has been combined with our durable NitroTAG® cryogenic label material. These thermal-transfer printable labels are built for long-term cryogenic storage in liquid nitrogen (-196°C / -321°F) and ultra-low temperature freezers (-80°C / -112°F).

SKU#	Inches (W x H)	mm (W x H)	Core	Labels/Roll	Colors
JTTA-566SBC1-2	0.35" circle + 0.8" x 0.6"	8.9 circle + 20.3 x 15.2	1"	2,000	WH YE GA BL OR PI
JTTA-566SBC3-4	0.35" circle + 0.8" x 0.6"	8.9 circle + 20.3 x 15.2	3"	4,000	
JTTA-560SBC1-2	0.437" circle + 0.94" x 0.5"	11.1 circle + 23.9 x 12.7	1"	2,000	
JTTA-560SBC3-4	0.437" circle + 0.94" x 0.5"	11.1 circle + 23.9 x 12.7	3"	4,000	
JTTA-562SBC1-2	0.437" circle + 1.125" x 0.75"	11.1 circle + 28.6 x 19.1	1"	2,000	
JTTA-562SBC3-4	0.437" circle + 1.125" x 0.75"	11.1 circle + 28.6 x 19.1	3"	4,000	



Writable NitroTAG® with SnapPEEL™

Temperature Range: -196°C to +110°C (-321°F to +230°F)

Writable cryo labels with SnapPEEL™ technology, packaged in a convenient, portable dispenser box for easy access, storage, and application. Designed for long-term cryo-preservation under cryogenic laboratory conditions.

SKU#	Inches (W x H)	mm (W x H)	Colors
JTRA-3512	0.437" circle + 0.94" x 0.5"	11.1 circle + 23.9 x 12.7	WH YE GA BL OR PI
JTRA-560	0.437" circle + 0.94" x 0.5"	11.1 circle + 23.9 x 12.7	MC1 or MC2



Laser CryoSTUCK® with SnapPEEL™

Temperature Range: -196°C to +100°C (-321°F to +212°F)

CryoSTUCK labels with SnapPEEL technology represent an innovative solution for identifying already frozen vials (as low as -80°C/-112°F). Our CryoSTUCK laser-printable labels work with most laser printers for sharp, smudge-proof results. They stick to frozen vials and tubes without overlap and can be written on with our Cryo-Markers. Free MS Word templates are available for quick set-up.

SKU#	Inches (W x H)	mm (W x H)	Format	Colors
LCS-125WH	0.437" circle + 0.94" x 0.5"	11.1 circle + 23.9 x 12.7	US Letter (8.5" x 11")	WH



Direct Thermal CryoSTUCK® with SnapPEEL™

Temperature Range: -196°C to +70°C (-321°F to +158°F)

These solvent-resistant cryogenic direct thermal printable labels will easily attach to already frozen vials, surfaces, and containers (as low as -80°C/-112°F), eliminating the need to thaw samples. Ideal for labeling temperature-sensitive specimens, they resist common lab chemicals like alcohols, xylene, and detergents. solvents.

SKU#	Inches (W x H)	mm (W x H)	Core	Labels/Roll	Colors
DTU-560SBNOTC1-2WH	0.437" circle + 0.94" x 0.5"	11.1 circle + 23.9 x 12.7	1"	2,000	WH
DTU-560SBNOTC3-2WH	0.437" circle + 0.94" x 0.5"	11.1 circle + 23.9 x 12.7	3"	2,000	



FreezerTAG™ with SnapPEEL™

Temperature Range: -80°C to +110°C (-112°F to +230°F)

FreezerTAG labels with SnapPEEL technology are designed for identifying individual PCR tubes. Ideal for long-term preservation in laboratory freezers, these PCR labels will adhere to wet surfaces and can withstand high temperatures, making them safe for use in PCR thermal cyclers. Thermal-transfer printable and available in a range of colors for easy coding.

SKU#	Inches (W x H)	mm (W x H)	Core	Labels/Roll	Colors
FJT-564SBC1	0.25" circle + 0.75" x 0.25"	6.4 circle + 19.1 x 6.4	1"	2,000	WH YE GA BL OR PI
FJT-564SBC3	0.25" circle + 0.75" x 0.25"	6.4 circle + 19.1 x 6.4	3"	4,000	

